	Performance and technical characteristics	
	Mains supply	230V~ 50/60Hz 66 W
Max flow rate	25 l/h (5.5 gph)	
Max suction head	2 m (6.6 ft)	
Max discharge head	10 m (33 ft)	
Protection	IP 54	
RoHS directive	Conform	
WEEE directive	Conform	
Pump dimensions	L 134 x W 171 x H 282 m	
Weight (including box)	±3.2 kg	
Packaging	Unitary	

### Description

The very high capacity of the PE 6250 pump and its 10 mm discharge tube enable removal of heavy condensate if required



### Kit contents

- Pump PE 6250
- 2 Screws and plugs
- 2 worm drive clamps
- Float detector ACC00601
- Fixing bracket

### Applications

Air conditioners up to 25 kW.  
 Console units  
 Fan coil units  
 Ceiling suspended units  
 Evaporators

### Accessories

	<b>ACC 00125, ACC 00126</b> Clear PVC tubing Ø 10 mm ACC 00125 : 25 m roll ACC 00126 : reinforced 25 m roll		<b>ACC 00601</b> Float detector Used to operate an additional alarm or switch on the pump
---	--	--	---

### The discharge flow is constant whatever the discharge or the suction head

Flow	25 l/h	Max suction head.	2 m	Max discharge head.	10 m
------	--------	-------------------	-----	---------------------	------